



SafetyLink is an innovative anchor company achieving success and keeping you safe whilst working at heights.

PRODUCT SHEET



FrogLine In Use

FROGLINE LIFELINE

Surface Mounted END Anchor



- ☞ Energy absorbing lifeline END anchor point.
- ☞ Specifically for use with permanent horizontal height safety lifeline systems, to be mounted on the surface of a metal roof profile.
- ☞ Suits pitches no greater than 25 degrees.
- ☞ Suits a multitude of roof profiles.
- ☞ Equipped with an engineered energy absorbing region to minimise loads on users and structures in the event of a fall.
- ☞ Intended for use with 8mm stainless steel cables.
- ☞ The FrogLine has been rigorously tested and manufactured in accordance with Australia and New Zealand Standard AS/NZS 1891.2 & European EN 795:2012, CEN/TS 16415:2013.

What am I used for?

A height safety system anchor point designed to be mounted on the surface of a metal roof profile as part of a permanent horizontal lifeline system as attachment points for the cable to start and terminate at. Fitted where it is difficult to access the underside of the roof.

The building or structure for the anchorages must be assessed by an engineer, unless it is clear to a competent person that the structure is adequate.

- ⚠ **MAXIMUM USER PER SYSTEM IS FOUR (4).**
- ⚠ **MAXIMUM PERSON PER SPAN IS TWO (2).**
- ⚠ **SEE SYSTEM INFORMATION FOR SITE SPECIFIC USE.**



Product Code: STAT. FROGSAL002

COMPONENTS: FROGLINE ALUMINIUM SURFACELINK END ANCHOR

FrogLine End Anchor	1
M16 x 35mm Stainless Steel Bolt	1
Washer: 70mm O.D. Black Plastic	1
SurfaceLink Plate: <i>Marine Grade Aluminium</i>	1
Washer: 70mm O.D. Black Plastic	1
Washer: 70mm O.D. 316 Stainless Steel	1
Nut: M16 316 Stainless Steel	1
Barrier Foam Tape	2

Product Code: STAT. FROGSUR002

COMPONENTS: FROGLINE STAINLESS STEEL SURFACELINK END ANCHOR

FrogLine End Anchor	1
M16 x 35mm Stainless Steel Bolt	1
SurfaceLink Plate: <i>316 Stainless Steel</i>	1
Washer: 70mm O.D. 316 Stainless Steel	1
Nut: M16 316 Stainless Steel	1
Barrier Foam Tape	2

Version 08.17



SafetyLink is an innovative anchor company achieving success and keeping you safe whilst working at heights.

PRODUCT SHEET




FrogLine In Use

POSITIONING LAYOUT

This is a guide only

All working at heights safety procedures must be complied with when installing SafetyLink height safety systems. For more information refer to your state or territories current legislation, regulations, policies and codes of practices.

Horizontal height safety lifelines must only be installed and used by competent people with relevant current height safety qualifications.



SAFETYLINK HEIGHT SAFETY SYSTEMS MUST ONLY BE INSTALLED AS PER OUR INSTALLATION GUIDES, TO STRUCTURES AS SPECIFIED IN THE INSTALLATION MANUAL FOR EACH PRODUCT. SHOULD ANY DOUBT EXIST IN REGARDS TO THE STRUCTURES INTEGRITY AN ENGINEER SHOULD BE CONSULTED.

Version 08.17



SafetyLink is an innovative anchor company achieving success and keeping you safe whilst working at heights.

PRODUCT SHEET



FrogLine
In Use

COPYRIGHT TERMS AND CONDITIONS

Copyright in the material contained on this disc/email belongs to SafetyLink Pty Ltd. You are authorised to reproduce this material subject to the following conditions:

1. No changes to the material may be made without SafetyLink Pty Ltd's prior written consent, which consent may be withheld, granted, or granted subject to conditions in SafetyLink Pty Ltd's discretion. Change includes any alteration, addition or deletion to the material or a part of the material that you reproduce.
2. You must ensure that any material you reproduce is marked "Copyright – SafetyLink Pty Ltd 2006".
3. Where you reproduce parts only of the material that must not cause the part reproduced to be misleading in any way or omit any important safety information.
4. You indemnify SafetyLink Pty Ltd against any claim arising out of your reproduction of the material on this disc/email or any part of it.
5. SafetyLink Pty Ltd can terminate this authority to reproduce this material on 7 day's notice in writing to you at your last known business address, for any reason. You must return this disc/email to SafetyLink Pty Ltd immediately after such a termination takes effect.

If you do not accept these conditions please return the disc/email to SafetyLink Pty Ltd. Your retention of the disc/email will otherwise be evidence of your acceptance of these conditions.

Patents

SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued.

Should you wish to know the progress of our intellectual property on a specific product please email us on ip@heightsafety.com.au and quote the product code.

