



SafetyLink is an innovative anchor company achieving success and keeping you safe whilst working at heights.

# PRODUCT SHEET

# PERMANENT LADDERS

Vertical Shuttle with Karabiner | Product Code: LADER001.10



- Vertical StaticLine Shuttle with Karabiner.
- Will track up or down with user vertically & self lock when a fall occurs.
- Can be installed/removed mid-line.
- For use on 8mm stainless steel or galvanised wire only.
- Must be used in conjunction with a personal energy absorber.
- Tested to AS/NZS1891.3.

## USING VERTICAL SHUTTLE ON LINE

- Vertical shuttle to be used with original karabiner supplied.
- Slide up the locking gate as indicated and attach the shuttle to the line. Release locking gate to secure to line.
- Ensure Karabiner is attached to personal fall arrest equipment.

## PROGRESSING ALONG THE LINE

- Always Progress the system manually. Do not progress in any vehicle or motioning device.
- Do not place any tools or equipment onto the line.

## DISCONNECTING FROM THE LINE

- If you are attaching to an alternative fall arrest system ensure you are attached to that system before disconnecting from the Vertical StaticLine.
- Slide up the locking gate as indicated and detach the shuttle to the line.

Assembling the SafetyLink® Permanent Ladder System is a simple exercise with SafetyLink's comprehensive installation guides. The individual ladder pieces join together with an outer coupling channel that is placed over the top of the inner channel and pop riveted into place.

**A FALL RESCUE PLAN SHOULD BE DEVELOPED PRIOR TO USING SAFETYLINK EQUIPMENT**



Catalogue



Manual

Version 08.17



SafetyLink is an innovative anchor company achieving success and keeping you safe whilst working at heights.


PRODUCT SHEET

# POSITIONING LAYOUT


*This is a guide only*

All working at heights safety procedures must be complied with when installing SafetyLink anchor points. For more information refer to your state or territories current legislation, regulations, policies and codes of practices.

## SPACING MUST BE NO GREATER THAN THE RAFTER LENGTH PLEASE CONTACT YOUR DISTRIBUTOR IF YOU ARE UNSURE



**ACCESS, LAYOUT & USE OF A SAFETYLINK ANCHOR SYSTEM**  
SafetyLink anchor points are positioned by calculating the pendulum effect, this limits the likelihood of a fall past the edge of the roof space.  
The pendulum effect still applies to a flat roof.



SAFETYLINK HEIGHT SAFETY SYSTEMS MUST ONLY BE INSTALLED AS PER OUR INSTALLATION GUIDES, TO STRUCTURES AS SPECIFIED IN THE INSTALLATION MANUAL FOR EACH PRODUCT. SHOULD ANY DOUBT EXIST IN REGARDS TO THE STRUCTURES INTEGRITY AN ENGINEER SHOULD BE CONSULTED.

Version 08.17



*SafetyLink is an innovative anchor company achieving success and keeping you safe whilst working at heights.*

**PRODUCT SHEET**

## COPYRIGHT TERMS AND CONDITIONS

Copyright in the material contained on this disc/email belongs to SafetyLink Pty Ltd. You are authorised to reproduce this material subject to the following conditions:

1. No changes to the material may be made without SafetyLink Pty Ltd's prior written consent, which consent may be withheld, granted, or granted subject to conditions in SafetyLink Pty Ltd's discretion. Change includes any alteration, addition or deletion to the material or a part of the material that you reproduce.
2. You must ensure that any material you reproduce is marked "Copyright – SafetyLink Pty Ltd 2006".
3. Where you reproduce parts only of the material that must not cause the part reproduced to be misleading in any way or omit any important safety information.
4. You indemnify SafetyLink Pty Ltd against any claim arising out of your reproduction of the material on this disc/email or any part of it.
5. SafetyLink Pty Ltd can terminate this authority to reproduce this material on 7 day's notice in writing to you at your last known business address, for any reason. You must return this disc/email to SafetyLink Pty Ltd immediately after such a termination takes effect.

If you do not accept these conditions please return the disc/email to SafetyLink Pty Ltd. Your retention of the disc/email will otherwise be evidence of your acceptance of these conditions.

### Patents

SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued.

Should you wish to know the progress of our intellectual property on a specific product please email us on [ip@heightsafety.com.au](mailto:ip@heightsafety.com.au) and quote the product code.

