



- ▲ SurfaceLink suits a multitude of roof profiles.
- ▲ For use as an **ABSEILING ANCHOR** on metal roof sheeting where access to the structure is difficult.
- ▲ Needs to be secured with 8x 8mm Rivets and 2x Hex Head Screws.
- ▲ The building or structure for the anchorages must be assessed by an engineer, unless it is clear to a competent person that the structure is adequate.

STANDARDS - Complies with AS/NZS 1891.4 and AS/NZS 5532-2013.

IMPORTANT NOTICE: Size 14.10x80mm All-Thread Hex Head Screws are supplied but if they don't penetrate the batten by a minimum of 35mm, longer screws need to be used.

WHAT AM I USED FOR? An anchor point designed for use on metal roof sheet profiles where access to timber is difficult. Adjustable design to suit different roof profiles.

COMPLETE UNIT - PRODUCT CODE: HSURFAB001+FIXINGS		Weight: 1.617kg	
Product Parts	Description	Qty	Material
EYEBOLT M16x26mm	Collared Eyebolt: M16x26mm	1	316 SS
ADV-PLATE-SS-305-H	Classic SurfaceLink Plate	1	316 SS
WASHER 70od-SS	Washer: 70mm OD	2	316 SS
WASHER M16_SPRING	Spring Washer: M16 316SS	1	316 SS
NUT M16	Nut: M16 316 Stainless Steel	1	316 SS
FOAM-TAPE 29 cm	Adhesive single sided tape	2	Foam
Rivet_8mm(27.7)	Aluminium 8mm Tri-fold Rivets	8	Aluminium
SCREW 14.10x80mm	14.10x80mm All-Thread Hex Head Screw with seal – Metal Tip	2	Steel



SCAN ME
safetylink.com



SCAN ME
Catalogue



SCAN ME
Safety Centre
Training

All products must be installed in accordance with SafetyLink's installation handbook, using only products supplied by SafetyLink Pty Ltd.



© 2018, SafetyLink Pty Ltd, Australia.

Patents: SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on ip@safetylink.com and quote the product code.

Doc ID: MKT-59 Version: 24.2